www.fhcmfg.com

Most fire incidents can be resolved by quick decisive action and the effective application of the correct extinguishing medium. Chief Fire Quick Attack Cart does the same for any hydrocarbon or any flammable chemical spill fire at any warehouse or petrochemical plants.

Quick Attack Cart is effortlessly portable and can be handled by one person. Equipped with solid rubber wheels or optional with the pneumatic wheels, which can be easily maneuvered on pavements or gravels.

Quick Attack Cart is designed with a rigid and compact Foam tank manufactured with SS316 sheets or optionally with GRP to store foam for adequate operational time.

QUICK ATTACK FOAM CART

QUICK ATTACK FOAM CART

Foam tank is provided with a breathing valve to balance pressure inside the tank with ambient pressure and isolate the tank from external humidity, dust or any other debris. Foam tank is also equipped with a level gauge to monitor foam level inside the tank plus a drain plug to flush foam or replace foam inside the tank.

Foam Monitor and master stream nozzle with an inbuilt educator is available with multiple options on inlet connections, materials, flow rates etc. designed for use with Class A & Class B foam, Including AFFF & Fluro-protein. Combination of straight stream and variable fog patterns are available.

FEATURES

- Nozzle is equipped with 3 % and 1% proportioning orifice as standard., it can be Interchangeable
- Fitted with cleared dial level gauge, to ensure level of foam in tank.
- Improved handling and mobility with greater operational stability.
- Rapid deployment of foam extinguishing agent.
- Low maintenance

QUICK ATTACK FOAM CART

SELF EDUCTING NOZZLE:
Available with,
- 150 GPM @ 100 PSI
-225 GPM @ 100 PSI
- 250 GPM @ 100 PSI
-350 GPM @ 100 PSI

MONITOR:
Customized manual/ Remote
Available with,
- 150 GPM
-225 GPM
- 250 GPM
-350 GPM

HOSE:
Available with,
-Synthetic Rubber
-Single Jacket
-Double Jacket
-UL/FM approved
-Brass coupling
-Aluminum coupling
-NH coupling
-BS coupling

LEVEL GAUGE:
Customized

SOLID WHEEL:
Customized
-10 x2.5” size
-15 x 3” size

FOAM TANK :
Customized tank capacity
25/40/50 Gallon , available in
- SS304
-SS316
- GRP
-Thermoplastic coated steel

WATER INLET:
Customized inlet ,
- NH coupling
- BS coupling

CHASSIS:
Customized with,
- Thermoplastic coated steel
- Alloy steel

Fire & Hazard Control Equipment Co. LTD. | Dammam 2nd Industrial Area | Kingdom of Saudi Arabia | Tel.: +966 13 8121095 | Email: sales@fhcmfg.com
Fire & Hazard Control makes every effort to ensure that the information and data provided are correct. However, we can accept no liability or guarantee that the information and data provided is up-to-date, correct and complete. This also applies for all other materials referred to. Nor is Fire & Hazard Control responsible for contents of such referenced information. Fire & Hazard Control reserves the right to modify or supplement the information or data provided without prior notice.